
DEEP

- High performing blackout fabric with a light sheen and black reverse
- Standard 100 by Oeko-Tex® certified, free from harmful substances
- Washable up to 60°
- Proven acoustic properties



APPLICATIONS

Not suitable:
SG 4905

FABRIC PROPERTIES

	Blackout
	Polyester
	325 g/m²
	0.45 mm
max.	290 cm
	295 cm
	295 cm

FEATURES / TECHNICAL PROPERTIES

	5
	Alpha-w = 0.30 / 0.55
	Flame retardant
	Applicable in humid areas
	Suitable for Wave
	Only with lined fabric
	Oeko-Tex
	Special colours from 240 m

WASHING INSTRUCTIONS

	30 -1%	60 -1%		P -0.5%		
	30 -1%					

FIRE PROTECTION

Class 1 (EN 13773)
Type B (BS 5867-2)
CAN/ULC-S109-14

OEKO TEX® STANDARD 100 S08-0170 Hohenstein HTTI

More information
silentgliss.com

Deep

OPTICAL AND SOLAR COEFFICIENTS (± 5%, DIN EN 410)

Colour	T_S	R_S	A_S	F_C	g_{tot}
01	0.0	4.1	95.9	0.89	0.64
02	0.0	4.1	95.9	0.89	0.64
03	0.0	4.1	95.9	0.89	0.64
05	0.0	4.1	95.9	0.89	0.64
06	0.0	4.1	95.9	0.89	0.64
07	0.0	3.2	96.8	0.90	0.65
08	0.0	3.2	96.8	0.90	0.65
10	0.0	3.9	96.1	0.89	0.64

T_S Solar transmission

A_S Solar absorption


g_{tot} Total g-value

R_S Solar reflectance


F_C Shading factor

Fc + gtot: Value calculated with glass: 0.72 / Ug = 1.6 W/m² K, DIN EN 13363-1

Deep




01



02




03



05



06



07



08



10

Colours shown are not binding

28/03/24